

2900s 2" System 14 Progressive Flow

Flecks "System 14" has been the industry standard progressive flow design for decades. Offering exceptional efficiency and flow rates from 2-700 GPM. The Fleck "System 14" is the choice for applications where efficiency and quality are paramount. Order 2-8 tanks!



System 14 Progressive Metered Softener	Tanks 2-8	≈Service/ Peak GPM 2 Tanks	≈Service/ Peak GPM 3 Tanks	≈Service/ Peak GPM 4 Tanks	≈Service/ Peak GPM 5 Tanks	≈Service/ Peak GPM 6 Tanks	≈Service/ Peak GPM 7 Tanks	≈Service/ Peak GPM 8 Tanks	Recommended Brine Tanks	Total Ft ³ per tank	≈Height
WS-291P-1252-1A96	12"x52"	2-15/35	2-30/70	2-45/105	2-60/135	2-75/170	2-90/205	2-105/240	18"x40"	2	66"
WS-291P-1354-1A96	13"x54"	3-18/40	3-36/80	3-54/120	3-72/160	3-90/200	3-108/240	3-126/280	18"x40"	2.5	68"
WS-291P-1465-1A96	14"x65"	3-21/45	3-42/90	3-63/135	3-84/180	3-105/225	3-126/270	3-147/315	18"x40"	3	79"
WS-291P-1665-1A96	16"x65"	4-27/50	4-54/100	4-81/150	4-108/200	4-135/250	4-162/300	4-189/350	24"x41"	4	79"
WS-291P-1865-1A96	18"x65"	5-35/60	5-70/120	5-105/180	5-140/240	5-175/300	5-210/360	5-245/420	24"x41"	5	79"
WS-291P-2162-1A96	21"x62"	7-48/70	7-96/140	7-144/210	7-192/280	7-240/350	7-288/420	7-336/490	24"x50"	6	80"
WS-291P-2460-1A96	24"x60"	9-62/80	9-124/160	9-186/240	9-248/320	9-310/400	9-372/480	9-434/560	24"x50"	7	79"
WS-291P-2472-1A96	24"x72"	9-62/80	9-124/160	9-186/240	9-248/320	9-310/400	9-372/480	9-434/560	24"x60"	9	89"
WS-291P-3072-6A96	30"x72"	15-90/90	15-180/180	15-270/270	15-360/360	15-450/450	15-540/540	15-630/630	30"x60"	14	99"
WS-291P-3657-6A96	36"x57"	21-90/100	21-180/200	21-270/300	21-360/400	21-450/500	21-540/600	21-630/700	30"x60"	12	83"
WS-291P-3672-6A96	36"x72"	21-90/100	21-180/200	21-270/300	21-360/400	21-450/500	21-540/600	21-630/700	39"x48"	18	99"