

PENTEK QUICK-CHANGE FILTRATION SYSTEMS

DESIGNED FOR EASY INSTALLATION AND CARTRIDGE CHANGE



Pentair Pentek[®] Quick-Change Filtration Systems are designed for easy installation and cartridge change. 1/4" or 3/8" push fittings, as well as 1/4" compression fittings, on the inlet and outlet sides of the filter head allow effortless installation.

The cartridge filter is easily changed with a quarter-turn of the filter. Water is automatically shut off during the change of the filter through the auto shut-off feature built into the filter head. This feature eliminates the need for additional shut-off valves to and from the filter system.

The Pentek Quick-Change Filter System offers several cartridge options to meet the demands of varying water conditions. The granular activated carbon cartridge offers chlorine taste and odor performance with low pressure drop. The EP carbon block filter offers superior chlorine taste and odor performance with 5 micron sediment reduction by mechanical means.

FEATURES/BENEFITS

Easy to install, easy filter change
Reversible metal brackets for 1, 2 or 3 cartridges
1/4-inch or 3/8-inch John Guest push-fit connections available

1/4-inch compression connections available for flex hose connections
Cartridge models to choose from to meet specific application needs

APPLICATIONS

Under-sink drinking water
Refrigerator/icemaker
Pre/post RO membrane
Vending machine

Ice machine
Coffee machine
Other OEM applications



QC10-EP, QC10-GAC, and QC10-CBR are Tested and Certified by NSF/ANSI to Standard 42.

EPA EST. NO. 090375-MEX-001

SPECIFICATIONS AND PERFORMANCE

PART #	MODEL #	CARTRIDGE COLOR	FILTER LIFE	FLOW RATE	RATING (NOMINAL)	1/4" THREADED	1/4" JG PUSH FIT	3/8" JG PUSH FIT
158682	QC10-CBR	White	500 gallons (1890 L)	0.5 gpm (1.9 Lpm)	0.5-micron*	•	•	•
158683	QC10-EP	White	1,500 gallons (5670 L)	0.5 gpm (1.9 Lpm)	5-micron**	•	•	•
158684	QC10-GAC	Blue	2,500 gallons (9460 L)	0.75 gpm (2.8 Lpm)	-	•	•	•
158723	QC10-TSGAC	Blue	1,700 gallons (6435 L)	0.75 gpm (2.8 Lpm)	-	-	•	•

*Reduces particles as small as this micron rating in size by mechanical means.

**Not Performance Tested or Certified by NSF.



WATER QUALITY SYSTEMS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2017 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands.

Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

310125 REV D FE17